

HYPRO KEY DIMENSIONAL SPECIFICATIONS

HI-PRO KEY NUMBER	WOODRUFF KEY NUMBER	DIAMETER OF CUTTER	THICKNESS KEY & CUTTER DECIMAL +.001 , -.000	LENGTH OF HI-PRO KEY	MAX. THICK OF LIP ON HI-PRO KEY +.000, -.005	MAX. HGHT HI-PRO KEY IN HUB +.000, -.005	MIN. DEPTH KEY SLOT FROM TOP OF SHAFT +.005, -.000	MAX.OVERALL HEIGHT OF HI-PRO KEY +.000, -.006
HP 402	1	1/2	.0625	17/32	.0284	.0313	.1748	.194
HP 403	2	1/2	.0938	17/32	.0421	.0469	.1611	.194
HP 404	3	1/2	.1250	17/32	.0564	.0625	.1468	.194
HP 503	4	5/8	.0938	21/32	.0421	.0469	.2079	.240
HP 504	5	5/8	.1250	21/32	.0564	.0625	.1937	.240
HP 505	6	5/8	.1563	21/32	.0711	.0781	.1789	.240
HP 506	61	5/8	.1875	21/32	.0856	.0938	.1645	.240
HP 604	7	3/4	.1250	25/32	.0570	.0625	.2555	.303
HP 605	8	3/4	.1563	25/32	.0711	.0781	.2414	.303
HP 606	9	3/4	.1875	25/32	.0854	.0938	.2272	.303
HP 608	91	3/4	.2500	25/32	.1126	.1250	.1999	.303
HP 705	10	7/8	.1563	15/16	.0713	.0781	.3038	.365
HP 706	11	7/8	.1875	15/16	.0856	.0938	.2895	.365
HP 707	12	7/8	.2188	15/16	.0999	.1094	.2751	.365
HP 708	A	7/8	.2500	15/16	.1140	.1250	.2610	.365
HP 709	121	7/8	.2500	15/16	.1140	.1250	.2610	.365
HP 806	13	1	.1875	1-1/16	.0856	.0938	.3520	.428
HP 807	14	1	.2188	1-1/16	.1003	.1094	.3372	.428
HP 808	15	1	.2500	1-1/16	.1149	.1250	.3226	.428
HP 810	B	1	.3125	1-1/16	.1422	.1563	.2954	.428
HP 812	152	1	.3750	1-1/16	.1689	.1875	.2687	.428
HP 813	141	1	.2500	1-1/16	.0625	.0726	.3225	.365
HP 814	131	1	.3125	1-1/16	.1242	.1663	.2054	.356
HP 906	16	1-1/8	.1875	1-3/16	.0859	.0938	.3985	.475
HP 907	17	1-1/8	.2188	1-3/16	.1003	.1094	.3841	.475
HP 908	18	1-1/8	.2500	1-3/16	.1150	.1250	.3694	.475
HP 910	C	1-1/8	.3125	1-3/16	.1433	.1563	.3411	.475
HP 1006	19	1-1/4	.1875	1-5/16	.0859	.0938	.4610	.537
HP 1007	20	1-1/4	.2188	1-5/16	.1003	.1094	.4466	.537
HP 1008	21	1-1/4	.2500	1-5/16	.1150	.1250	.4319	.537
HP 1010	D	1-1/4	.3125	1-5/16	.1433	.1563	.4036	.537
HP 1012	E	1-1/4	.3750	1-5/16	.1719	.1875	.3750	.537
HP 1108	22	1-3/8	.2500	1-7/16	.1153	.1250	.4785	.584
HP 1110	23	1-3/8	.3125	1-7/16	.1433	.1563	.4505	.584
HP 1112	F	1-3/8	.3750	1-7/16	.1719	.1875	.4219	.584

HYPRO KEY DIMENSIONAL SPECIFICATIONS

HI-PRO KEY NUMBER	WOODRUFF KEY NUMBER	DIAMETER OF CUTTER	THICKNESS KEY & CUTTER DECIMAL +.001, -.000	LENGTH OF HI-PRO KEY	MAX. THICK OF LIP ON HI-PRO KEY +.000, -.005	MAX. HGHT HI-PRO KEY IN HUB +.000, -.005	MIN. DEPTH KEY SLOT FRO TOP OF SHAFT +.005, -.000	MAX.OVERALL HEIGHT OF HI-PRO KEY +.000, -.006
HP 1208	24	1-1/2	.2500	1-9/16	.1153	.1250	.5254	.631
HP 1210	25	1-1/2	.3125	1-9/16	.1446	.1563	.4961	.631
HP 1212	G	1-1/2	.3750	1-9/16	.1747	.1875	.4659	.631
HP 1306	226	1-5/8	.1875	1-3/8	.0838	.0938	.3225	.428
HP 1308	227	1-5/8	.2500	1-3/8	.1153	.1250	.2910	.428
HP 1310	228	1-5/8	.3125	1-3/8	.1463	.1563	.2600	.428
HP 1312	229	1-5/8	.3750	1-3/8	.1773	.1875	.2290	.406
HP 1706A	126	2-1/8	.1875	1-5/8	.0838	.0938	.3225	.396
HP 1708A	127	2-1/8	.2500	1-9/16	.1153	.1250	.2910	.396
HP 1710A	128	2-1/8	.3125	1-9/16	.1463	.1563	.2600	.396
HP 1712A	129	2-1/8	.3750	1-1/2	.1773	.1875	.2290	.396
HP 1706B	26	2-1/8	.1875	1-7/8	.0838	.0938	.4475	.521
HP 1708B	27	2-1/8	.2500	1-13/16	.1153	.1250	.4160	.521
HP 1710B	28	2-1/8	.3125	1-25-32	.1463	.1563	.3850	.521
HP 1712B	29	2-1/8	.3750	1-3/4	.1775	.1875	.3538	.521
HP 2208A	RX	2-3/4	.2500	2-3/16	.1158	.1250	.4780	.584
HP 2210A	SX	2-3/4	.3125	2-3/16	.1463	.1563	.4475	.584
HP 2212A	TX	2-3/4	.3750	2-1/8	.1775	.1875	.4163	.584
HP 2214A	UX	2-3/4	.4375	2-1/16	.2088	.2188	.3850	.584
HP 2216A	VX	2-3/4	.5000	2-1/16	.2408	.2500	.3530	.584
HP 2208B	R	2-3/4	.2500	2-7/16	.1150	.1250	.6350	.750
HP 2210B	S	2-3/4	.3125	2-3/8	.1463	.1563	.6037	.750
HP 2212B	T	2-3/4	.3750	2-3/8	.1770	.1875	.5730	.750
HP 2214B	U	2-3/4	.4375	2-5/16	.2088	.2188	.5412	.750
HP 2216B	V	2-3/4	.5000	2-5/16	.2400	.2500	.5100	.750
HP 2812	30	3-1/2	.3750	3	.1775	.1875	.7600	.938
HP 2814	31	3-1/2	.4375	3	.2088	.2188	.7287	.938
HP 2816	32	3-1/2	.5000	3	.2400	.2500	.6975	.938
HP 2818	33	3-1/2	.5625	2-7/8	.2712	.2813	.6662	.938
HP 2820	34	3-1/2	.6250	2-7/8	.3025	.3125	.6350	.938
HP 2822	35	3-1/2	.6875	2-13/16	.3338	.3438	.6037	.938
HP 2824	36	3-1/2	.7500	2-13/16	.3650	.3750	.5725	.938